

GRIFLUBE SPINDLE OILS

Hill and Griffith's **GRIFLUBE SPINDLE OIL** series of lubricants are light bodied oils which are designed for the lubrication and protection of high-speed spindles in machine tools and textile machinery. These high-quality oils are specially compounded to provide exceptional resistance to wear, deposit formation, and fortified to minimize oxidation and corrosion.

TYPICAL SPECIFICATIONS:

PRODUCT	API	POUR	FLASH	VISCOSITY	VISCOSITY	CINNINNATI	ISO	PACKAGING
	Gravity	Point	Point	100°F SUS	Index	Milacron	VG	
SPINDLE 10	36.1	32°F	310°	60	95	P-62	10	Totes & Drums
SPINDLE 22	32.0	27°F	370°F	108	95	P-45	22	Drums & Pails

GRIFLUBE SPINDLE 10 is normally recommended for spindles operating in excess of 3600 RPM, while **GRIFLUBE SPINDLE 22** is designed for speeds less than 3600 RPM.

HEALTH & SAFETY

All reasonable care has been taken to ensure that the information contained in this publication is accurate as the date of printing, however, such information might change due to changes in the formulation blend occurring subsequent to the date of printing. The MSDS must be consulted for appropriate information regarding storage, safe handling and storage.

